

Application No.: 09/855,343
Docket No.: DP6760US

Page 2

BEST AVAILABLE COPY**In the Claims**

Please amend the claims as follows:

1. (currently amended) A melt spinning apparatus for spinning continuous polymeric filament comprising:
 - (a) a spinneret having a plurality of capillaries;
 - (b) a polymer delivery system which is arranged to communicate with said spinneret and deliver molten polymer there through to produce a continuously moving array of molten polymeric filaments corresponding to the arrangement of capillaries in the spinneret;
 - (c) a quench zone positioned below said spinneret and arranged to receive and cool the array of molten filaments as they move through by passing a cooling gas inward with respect to the array of moving filaments; and
 - (d) a finish applicator positioned inside or below the quench zone to apply an amount of finishing liquid to the array, wherein said finish applicator comprises:
 - (i) a base plate having a peripheral edge which corresponds to the cross-section of the array of moving molten filaments; and
 - (ii) a tapered shaped body portion, the tapered shaped body having an angle beta (β) in the range of about 45 degrees to about 170 degrees for smoothly deflecting accumulated quench air from inside the filament array to outside the array and having a top and bottom concentric therewith and connected to said base plate, wherein said bottom corresponds in shape to the shape defined by the peripheral edge of the base plate, and ~~the~~ having a surface formed by a plurality of lines drawn between said top and said bottom ~~tapers~~ tapering outwardly with respect to the direction of movement of the filament array.

Application No.: 09/855,343
Docket No.: DP6760US

Page 3

2. (original) The apparatus of claim 1, further comprising a means for moving the finish applicator into and out of the array of filament.
3. (original) The apparatus of claim 1, wherein said quench zone is a radial, cross-flow, or pneumatic quench zone.
4. (original) The apparatus of claim 1, wherein said applicator is a conical-shaped finish applicator.
5. (original) The apparatus of claim 1, wherein the finish applicator includes a filament contact surface coated with ceramic oxide.
6. (original) The apparatus of claim 1, wherein said finish applicator comprises one or more peripheral finish delivery slots that communicates with a peripheral fiber contact surface.
7. (original) The apparatus of claim 1, wherein said finish applicator is positioned a distance ranging from 120 mm to 200 mm below said spinneret.
8. (original) The apparatus of claim 1, wherein said finish applicator is positioned a distance ranging from 200 mm to 400 mm below said quench zone.
9. (original) The apparatus of claim 1, wherein the array of the filaments being annular comprise an inner and an outer filament array diameter that determine the diameter of said finish applicator in a range of 70% to 120% of the outer filament array diameter.
10. (currently amended) A melt spinning apparatus for spinning continuous polymeric filaments, comprising a finish applicator to apply an amount of finishing liquid to an array of filaments, positioned inside or below a quench zone that is

Application No.: 09/855,343
Docket No.: DP6760US

Page 4

arranged to receive a stream of cooling gas directed radially inward, wherein said finish applicator comprises:

- (i) a base plate having a peripheral edge which corresponds to the cross-section of the array of moving molten filaments; and
- (ii) a tapered shaped body portion, the tapered shaped body having an angle beta (β) in the range of about 45 degrees to about 170 degrees for smoothly deflecting accumulated quench air from inside the filament array to outside the array and having a top and bottom concentric therewith and connected to said base plate, wherein said bottom corresponds in shape to the shape defined by the peripheral edge of the base plate, and [the] having a surface formed by a plurality of lines drawn between said top and said bottom [tapers] tapering outwardly with respect to the direction of movement of the filament array.

11. (cancelled)

12. (previously presented) The melt spinning apparatus of claim 10, wherein the finish applicator further comprises a peripheral delivery slot for delivering the finishing liquid to the filament array, and wherein said peripheral delivery slot communicates with a peripheral fiber contact surface on an outer surface of the body portion.

13. (previously presented) The melt-spinning apparatus of claim 12, wherein the finish applicator further comprises an arm having channels for delivery and drainage of said finishing liquid, wherein said arm supports said finish applicator and further wherein said arm is connected to said peripheral delivery slot.

14. (previously presented) The melt spinning apparatus of claim 10, wherein said finish applicator is mounted on a linear motion device.

Application No.: 09/855,343
Docket No.: DP6760US

Page 5

15. (cancelled)

16. (cancelled)

17. (cancelled)

18. (cancelled)

19. (cancelled)

20. (cancelled)

21. (cancelled)

22. (cancelled)

23. (cancelled)

24. (cancelled)

25. (cancelled)

26. (cancelled)

27. (currently amended) A melt spinning apparatus for spinning continuous polymeric filaments, comprising a finish applicator to apply an amount of finishing liquid to an array of filaments, positioned inside or below a quench zone that is arranged to receive a stream of cooling gas directed inward, wherein said finish applicator comprises

Application No.: 09/855,343

Docket No.: DP6760US

Page 6

- (i) a base plate having a peripheral edge which corresponds to the cross-section of the array of moving molten filaments; and
- (ii) a tapered shaped body portion, the tapered shaped body having an angle beta (β) in the range of about 45 degrees to about 170 degrees for smoothly deflecting accumulated quench air from inside the filament array to outside the array and having a top and bottom concentric therewith and connected to said base plate, wherein said bottom corresponds in shape to the shape defined by the peripheral edge of the base plate, and the having a surface formed by a plurality of lines drawn between said top and said bottom ~~tapers~~ tapering outwardly with respect to the direction of movement of the filament array.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.